Quick Disconnect Couplings and Plugs Industrial Interchange



Quick Disconnect Couplings and Plugs by Kuriyama are semi-automatic and rated to 300 PSI when used with 1/4" and 3/8" ID air hoses.



Coupler with Male Thread

Part	Body	Thread	Weight	Standard
Number	Size	Size	Each	Package*
QDAC-4MC	1/4"	1/4 "	0.23	10
QDAC-6MC	1/4"	3/ ₈ "	0.23	10



Plug with Male Thread

Part	Body	Thread	Weight	Standard
Number	Size	Size	Each	Package*
QDAP-4MP	1/4"	1/4"	0.05	10
QDAP-6MP	1/4"	3/ ₈ "	0.05	10



Coupler with Female Thread

Part	Body	Thread	Weight	Standard
Number	Size	Size	Each	Package*
QDAC-4FC	1/4"	1/ ₄ "	0.23	10
QDAC-6FC	1/4"	3/ ₈ "	0.23	10



Plug with Female Thread

Part	Body	Thread	Weight	Standard
Number	Size	Size	Each	Package*
QDAP-4FP	1/4"	1/4 "	0.05	10
QDAP-6FP	1/4"	3/8 "	0.05	10



Coupler with Hose Barb

Part	Body	Barb	Weight	Standard
Number	Size	Size	Each	Package*
QDAC-4HC	1/4"	1/ ₄ "	0.23	10
QDAC-6HC	1/4"	3/ ₈ "	0.23	10



Part Number	Body Size	Barb Size	Weight Each	Standard Package*
QDAP-4HP	1/4"	1/4"	0.05	10
QDAP-6HP	1/4"	3/8"	0.05	10

^{*}All Quick Disconnect Couplings and Plugs are sold in full standard packages only.

KCPPL0107

Ground Joints

Couplings and Clamps - Zinc Plated



Hose Stem with Wing Nut and Female Spud

	-		•	
	Part Number	Size	Weight Each	Standard Carton
	GJ-050 GJ-075 GJ-100	1/2" 3/4" 1"	0.75 1.86 1.81	50 25 30
	GJ-125 GJ-150 GJ-200	1 ¹ / ₄ " 1 ¹ / ₂ " 2"	3.73 3.68 5.69	15 15 10
	GJ-250 GJ-300 GJ-400	2 ¹ / ₂ " 3" 4"	12.59 15.85 28.46	4 4 2

Hose Stem Only

	- ,			
	Part Number	Size	Weight Each	Standard Carton
	GJS-050 GJS-075 GJS-100	1/2" 3/4" 1"	0.18 0.55 0.51	200 100 100
	GJS-125 GJS-150 GJS-200	1 ¹ / ₄ " 1 ¹ / ₂ " 2"	1.17 1.30 1.72	32 35 25
	GJS-250 GJS-300 GJS-400	2 ¹ / ₂ " 3" 4"	3.70 4.83 8.95	10 8 4