

Boston Performer II



Tube: Nitrile

Reinforcement: Fiber, 1 or 2 Braid

Cover: Vinyl Nitrile

Color: Red

Temperature Range: -40°F To +180°F

Type Of Branding: Ink Print

Working Pressure: 225-300 PSI

Type Of Coupling: 'U' Series, 430 'U', Barbed Inserts, Quick Acting, Long Shank, Series or Steel Nipple, Clamps—Interlocking, Bolt, Band or Wire.

Features:

- Vinyl nitrile cover
- Nitrile tube (RMA Class A)
- Continuous permanent brand
- Multi-purpose hose
- High working pressure
- Braided reinforcement

Advantages:

- Abrasion, oil, and weather resistant
- High oil resistance
- Easy identification
- For many applications
- Better coupling retention for impulse applications

Markets:

- Assembly/Manufacturers
- Construction Industry
- Forest Industry
- Metal Working
- Mining
- Ship Building
- Plastic Molding

Applications:

- Pneumatic tools on production line
- Provide power to air operated equipment
- Convey air and water

PRODUCT NUMBER	NOMINAL I.D. (IN.) (MM)	BRAID	NOMINAL O.D. (IN.) (MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAX. WORKING PRESS. (PSI)	STANDARD REELS (FT)
H11604-550R	1/4 6.3	1	1/2 12.7	10	225	550
H11504	1/4 6.3	2	19/32 15.1	15	300	50
H11504-550R						550
H11605-550R	5/16 7.9	1	5/8 15.9	14	225	550
H11505	5/16 7.9	2	21/32 15.9	14	300	50
H11505-550R						550
H11606-550R	3/8 9.5	1	21/32 16.7	15	225	550
H11506	3/8 9.5	2	3/32 18.3	19	300	50
H11506-550R						550
H11608-550R	1/2 12.7	1	13/16 20.6	21	225	550
H11508	1/2 12.7	2	7/8 22.2	27	300	50
H11508-550R						550
H11512	3/4 19.1	2	1-5/32 29.4	41	300	50
H11512-550R						550
H11516	1 25.4	2	1-7/16 36.5	46	250	50
H11516-300R						300
H11520	1-1/4 31.8	2	1-3/4 44.5	65	225	50
H11520-300R						300
H11524	1-1/2 38.1	2	2 50.8	82	225	50
H11524-300R						300