Refer to warnings and safety information on pages 3-4 and page 71.

Boston Hot Tar Pumping

Tube: Nitrile (RMA Class A)
Reinforcement: Wire, 2 Braid
Cover: CPE/Pinpricked
Color: Black
Temperature Range: +350°F
Type Of Branding: Impression
Working Pressure: 250 PSI
Type Of Coupling: Wolf Coupling, 430 'U' Series, Interlocking or Steel Nipple. Clamps—Interlocking

Features:
- CPE cover
- Nitrile tube
- Continuous permanent brand/black cover

Advantages:
- Abrasion, oil, heat, and weather resistant
- Oil and heat resistant; handles intermittent temperatures of hot tar up to 400°F
- Easy identification
- Assures proper use

Markets:
- Road Construction
- Roof Construction

Applications:
- Convey hot tar/asphalt in road projects
- Convey hot tar

PRODUCT NUMBER	NOMINAL I.D. (IN.)	(MM)	BRAID	NOMINAL O.D. (IN.)	(MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	(MM)	STANDARD LENGTH (FT)
H960316	1	25.4	2	19/16	39.7	90	250	12	304.8	50
H960316-100										100
H960316-150										150