

Boston Grey Food Transfer



Tube: Vinyl Nitrile, FDA Approved Materials

Reinforcement: Fiber, 4 Spiral and Helical Wire

Cover: Vinyl Nitrile

Color: Grey

Temperature Range: -40°F to +180°F

Type Of Branding: Impression

Suction: Full Vacuum

Working Pressure: 150 PSI (Depending on coupling)

Type Of Coupling: Cam and Groove, Combination Nipple or Swaged/Crimped/Internal Expanded. Clamps—Band.

Features:

- Vinyl nitrile cover
- Vinyl nitrile tube
- Continuous permanent brand
- Grey cover
- Smooth bore

Advantages:

- Abrasion, animal fat, oil and weather resistant
- Animal and vegetable oil resistant
- Easy identification
- Meets FDA requirements
- Rapid fluid flow
- Easy to clean

Markets:

- Food Industry
- Tank Truck
- Rail Car
- In-plant

Applications:

- Transfer by pumping, suction, and discharge of non-dairy food products
- Transfer of bulk liquid, sugar, syrups, and vegetable oils from tank trucks to candy manufacturers, bottling plants, processors, etc.

PRODUCT NUMBER	NOMINAL I.D. (IN.)	I.D. (MM)	SPIRAL	NOMINAL O.D. (IN.)	O.D. (MM)	APPROX. LBS. WEIGHT PER 100 FT.	MAXIMUM WORKING PRESS. (PSI)	MINIMUM BEND RADIUS (IN.)	RADIUS (MM)	STANDARD LENGTH (FT)
H038424-100	1-1/2	38.1	4	2-1/8	54.0	120	150	4	101.6	100
H038432-100	2	50.8	4	2-5/8	66.7	145	150	5	127.0	100
H038448-100	3	76.2	4	3-5/8	92.1	220	150	9	228.6	100
H038464-100	4	101.6	4	4-5/8	117.5	315	150	11	279.4	100

White cover available as a made-to-order.