

CLEANING EQUIPMENT

NEPTUNE™ 3000



APPLICATION:	For use on pressure washer machines with working pressures up to 3000 psi.
CONSTRUCTION	
TUBE:	Nitrile synthetic rubber
COVER:	Black, Blue, Yellow or Gray oil-resistant synthetic rubber, RMA Class B (Medium Oil Resistance)
REINFORCEMENT:	Braided (1) steel wire
TEMPERATURE:	-20°F to 250°F (-29°C to 121°C)
PACKAGING:	500' reel, maximum 3 pieces, 50' increments
BRANDING:	Continuous brand "Neptune 3000 by Goodyear" 3/8" 3000 psi WP. Made in USA."
COUPLINGS:	Use Goodyear's pressure washing fittings with this product. See page 235 for available sizes. Refer to Goodyear's Hose Assembly Manual for crimp procedures. Coupled lengths with MxMS fittings and Kink Guards available.
NON-STOCK/SIZES:	Refer to page 300 for special production run minimum requirements.
ORDER CODES:	539-085 (black) 539-089 (blue) 539-104 (yellow) 539-090 (gray)

ID		NOM. OD		MAX. WP		WEIGHT	
<i>in.</i>	<i>mm.</i>	<i>in.</i>	<i>mm.</i>	<i>psi.</i>	<i>Mpa.</i>	<i>lb./ft.</i>	<i>kg./m.</i>
1/4	6.4	0.53	13.5	3000	20.69	0.16	0.24
3/8	9.5	0.69	17.5	3000	20.69	0.24	0.36
1/2	12.7	0.82	20.8	3000	20.69	0.32	0.48

Note: Not recommended for steam service.